## ZERO-NET TO Sightline Vent

The **Zero Sightline Vent** combines sleek aesthetics with excellent thermal performance. It is designed to seamlessly integrate with the curtain wall system, appearing visually discrete and smooth when closed. This creates a continuous, uninterrupted look in the design. Encompassing the FortMax<sup>™</sup> thermal barrier, the Zero Sightline Vent can achieve assembled U-values as low as 0.18.

## Chelsea Veteran's Home

OPERABLE WINDOW

Chelsea, MA Payette





## **FEATURES**

- Can be integrated into all Zero•Net™ systems
- Field or shop glazed
- Incorporates FreMarq's FortMax™ thermal barrier
- Industry-leading U-values as low as 0.18 based on NFRC gateway sizes
- Can accommodate infills up to 1 3/4" for greater thermal performance
- Furnished in captured or SSG

Product	Glass	Center of Glass U-Value	Assembled U-Value	Description
Zero Sightline Vent	1" Single Low E	0.24	0.322	NFRC Size
Zero Sightline Vent	1" Double Low E	0.195	0.263	NFRC Size Custom Single Vision 47" x 59"
Zero Sightline Vent	1" Double Low E	0.195	0.305	NFRC Size Projected Awning Single 59" x 23"
Zero Sightline Vent	Triple	0.134	0.245	NFRC Size Projected Awning Single 59" x 23"
Zero Sightline Vent	VIG	0.049	0.241	NFRC Size Projected Awning Single 59" x 23"